MANUAL & INTEGRATED PULLERS | OEM CROSS-REFERENCE: ENERPAC SELF-CENTERING PULLERS EQUIVALENT

HAP-C Series Sync Self-Centering Pullers

Synchronous auto-centering mechanical and hydraulic pullers rated for 700 Bar (10,000 PSI), engineered for effortless, non-destructive disassembly of press-fitted components across 7 to 60 Ton capacities.



View Online & Get Quote ->

RATED CAPACITY **7 - 60 Metric Tons (69 to 588 kN)**	OPERATING PRESSURE **700 Bar (10,000 PSI)**	PULLER CONFIGURATION **Mechanical Screw (7-30T) & Hydraulic Hollow Ram (10-60T)**
MAXIMUM SPREAD **60 to 920 mm (2.36 to 36.2 in)**	MAXIMUM REACH **225 to 727 mm (8.86 to 28.6 in)**	HYDRAULIC PACKAGE **Hollow Ram Cylinder, Hand Pump, Hose & 61mm Gauge**

Model Number	Actuation Type	Pulling Capacity [Ton (kN)]	Reach A [mm]	Spread B [mm]	Hand Pump	Hydraulic Cylinder	Weight [kg]
MAP-C7	Mechanical	7 (69)	225	60 - 280	-	-	4.5
MAP-C10	Mechanical	10 (98)	385	60 - 430	-	-	10.5
MAP-C20	Mechanical	20 (196)	480	60 - 500	-	-	25.5
MAP-C30	Mechanical	30 (294)	585	60 - 600	-	-	58.0
HAP-C10	Hydraulic	10 (98)	296	60 - 430	HPM-S-900A	HSCH-121	8.9
HAP-C20	Hydraulic	20 (196)	340	60 - 500	HPM-S-900A	HSCH-202	18.25
HAP-C30	Hydraulic	30 (294)	420	60 - 600	HPM-S-900A	HSCH-302	36.4
HAP-C60	Hydraulic	60 (588)	727	60 - 920	HPM-S-2300A	HSCH-603	86.5