MANUAL & INTEGRATED PULLERS | OEM CROSS-REFERENCE: ENERPAC INTEGRATED BHP EQUIVALENT

HAP-I Series Integrated Self-Contained Pullers

Self-contained integrated hydraulic pullers rated for 700 Bar (10,000 PSI), engineered for one-person bearing extraction, gear disassembly, and shaft pulling across 4 to 50 Ton capacities.



View Online & Get Quote ->

RATED CAPACITY **4 - 50 Metric Tons**	OPERATING PRESSURE **700 Bar (10,000 PSI)**	PUMP MECHANISM **Integrated Manual Pump with 360° Rotating Handle**
STROKE RANGE **60 - 111 mm**	JAW CONFIGURATION **Interchangeable 2/3-Jaw Shared Setup**	SAFETY FEATURE **Internal Overload Relief Valve (Two-Speed on 20-50T)**

Model Number	Pulling Capacity [Ton]	Reach [mm]	Max. Spread [mm]	Stroke [mm]	Speed Mode	Weight [kg]
HAP-I-4	4	185	255	60	Single-Speed	4.5
HAP-I-6	6	220	330	70	Single-Speed	5.5
HAP-I-8	8	230	350	85	Single-Speed	6.5
HAP-I-12	12	270	375	85	Single-Speed	8.0
HAP-I-20	20	360	520	110	Two-Speed	22.0
HAP-I-30	30	395	550	111	Two-Speed	32.0
HAP-I-50	50	460	615	111	Two-Speed	45.0