SAFETY CAGE SELF-LOCK PULLERS | OEM CROSS-REFERENCE: ENERPAC SELF-LOCKING PULLERS EQUIVALENT

HAP-L Series Hydraulic Self-Locking Puller Sets

Hydraulic safety cage puller sets rated for 700 Bar (10,000 PSI) with positive anti-slip locking cage and long-stroke cylinders across 5 to 50 Ton capacities.



View Online & Get Quote ->

RATED CAPACITY	OPERATING PRESSURE	LOCKING MECHANISM
5 - 50 Metric Tons (49 to 490 kN)	700 Bar (10,000 PSI)	Positive Mechanical Safety Cage with Anti-Slip Lock
CYLINDER STROKE	**MAXIMUM SPREAD**	**MAXIMUM REACH**
127 to 362 mm Long-Stroke Cylinders	178 to 635 mm (7.0 to 25.0 in)	152 to 355 mm (5.98 to 13.98 in)

Set Model	Puller Unit	Pulling Capacity [Ton]	Jaws	Spread [mm]	Reach [mm]	Stroke [mm]	Oil Cap. [cm³]	Cylinder	Manual Pump	Hose	Gauge	Gauge Adaptor	Puller Wt [kg]
HAP-LS106E	HAP-L106	5	3	178	152	127	83	HSC-55	HPM-S-900A	HSH-7206C	HSG-2510	HGA-003	8.9
HAP-LS108E	HAP-L108	10	3	304	203	156	226	HSC-106	HPM-S-900A	HSH-7206C	HSG-2510	HGA-003	10.0
HAP-LS110E	HAP-L110	15	3	381	245	254	516	HSC-1510	HPM-S-900A	HSH-7206C	HSG-2510	HGA-003	12.0
HAP-LS113E	HAP-L113	25	3	457	304	362	1202	HSC-2514	HPM-S-2300A	HSH-7206C	HSG-2510	HGA-003	15.0
HAP-LS116E	HAP-L116	50	3	635	355	337	2399	HSC-5013	HPM-S-4500	HSH-7206C	HSG-2510	HGA-003	26.0