MANUAL & INTEGRATED PULLERS | OEM CROSS-REFERENCE: ENERPAC SEPARATE BHP EQUIVALENT

HAP-S Series Separate Heavy-Duty Hydraulic Pullers

Separate heavy-duty hydraulic pullers rated for 700 Bar (10,000 PSI) with external pump coupling, engineered for large-scale shaft disassembly across 4 to 100 Ton capacities.



View Online & Get Quote ->

RATED CAPACITY **4 - 100 Metric Tons (39 to 980 kN)**	OPERATING PRESSURE **700 Bar (10,000 PSI)**	ACTUATION SYSTEM **Separate External Hydraulic Pump Coupled via Quick Hose**
MAXIMUM SPREAD **315 to 1,500 mm (12.4 to 59.1 in)**	MAXIMUM REACH **190 to 680 mm (7.48 to 26.8 in)**	JAW METALLURGY **Forged Alloy Steel with Anti-Rust Manganese Phosphate Plating**

Model Number	Pulling Capacity [Ton]	Reach [mm]	Max. Spread [mm]	Stroke [mm]	Weight [kg]
HAP-S4	4	190	315	60	8.9
HAP-S6	6	230	390	70	10.0
HAP-S8	8	280	460	85	12.0
HAP-S12	12	300	515	85	15.0
HAP-S20	20	325	520	111	26.0
HAP-S30	30	415	620	111	36.0
HAP-S50	50	455	860	159	140.0
HAP-S75	75	455	1000	159	175.0
HAP-S100	100	680	1500	168	250.0