HBP-G Series Hydraulic Grip Puller Sets

2/3-jaw hydraulic grip puller sets rated for 700 Bar (10,000 PSI), supplied with hollow cylinder, hand pump, hose, pressure gauge, and adaptor for press-fitted shaft bearings, pulleys, and gears across 8 to 50 Ton capacities.



View Online & Get Quote ->

RATED CAPACITY
8 - 50 Metric Tons

OPERATING PRESSURE
700 Bar (10,000 PSI)

JAW VERSATILITY
Quick Conversion Between 2-Jaw and 3-Jaw Setups

MAXIMUM SPREAD
Spread 249 to 1,100 mm

MAXIMUM REACH
Reach 252 to 700 mm

HYDRAULIC PACKAGE
Hollow Cylinder, Hand Pump, Hose, Gauge & Adaptor

Model Number	Pulling Capacity [Ton]	Locking Puller	Max Spread 2-Jaw [mm]	Max Spread 3-Jaw [mm]	Max Reach [mm]	Hollow Cylinder	Hand Pump	Saddle	Hose	Gauge	Gauge Adaptor	Jaw Thickness [mm]	Jaw Width [mm]	Adjusting Screw Thread	Screw Length [mm]	Set Weight [kg]
HBP-152	8	HBP-1762	249	249	252	HSCH-121	HPM-S-280	-	HSH-7206C	HSG-2510	HGA-011	15	23	3/4"-16 UNF	400	22
HBP-251G	20	HBP-252	400	499	300	HSCH-202	HPM-S-900A	HP-2015	HSH-7206C	HSG-2510	HGA-003	20	27	1"-8 UNC	675	56
HBP-351G	30	HBP-352	593	800	387	HSCH-302	HPM-S-900A	HP-3015	HSH-7206C	HSG-2510	HGA-003	24	38	1-1/4"-7 UNC	795	91
HBP-551G	50	HBP-552	899	1100	700	HSCH-603	HPM-S-2300A	HP-5016	HSH-7206C	HSG-2510	HGA-003	30	39	1-5/8"-5.5 UNC	975	160