GENERAL PURPOSE & LOW HEIGHT CYLINDERS | OEM CROSS-REFERENCE: ENERPAC RLS SERIES EQUIVALENT

HSCT Series Multi-Stage Telescopic Cylinders

Single-acting load-return multi-stage telescopic flat hydraulic cylinders rated for 700 Bar (10,000 PSI), engineered for extended stroke lifting in extremely confined overhead clearances without repetitive shimming across 10 to 50 Metric Ton capacities.



View Online & Get Quote ->

RATED CAPACITY	OPERATING PRESSURE	ACTION & RETURN
10 - 50 Metric Tons	700 Bar (10,000 PSI)	Single-Acting, Load Return
STROKE RANGE	**COLLAPSED HEIGHT**	**PLUNGER & SURFACE**
25 - 64 mm (Multi-Stage Telescopic)	42 - 66 mm (Ultra-Low Flat Profile)	Sequential Multi-Tier Plunger with Hardened Coating

Model	Capacity @10,000 PSI (700 bar) [Metric Ton]	Stroke [mm]	Oil Capacity [cm3]	Closed Height (A) [mm]	Extended Height (B) [mm]	Outside Diam. (D) [mm]	Weight [kg]
HSCT-100	10	25	22	42	67	82×55	1.5
HSCT-200	20	26	41	51	77	101×76	2.4
HSCT-300	30	53	58	58	111	117×95	4.5
HSCT-500	50	64	113	66	130	140×114	7.0