HTJ Series Heavy-Duty Hydraulic Toe Jacks

Heavy-duty hydraulic toe jacks (2 to 25 Ton toe / 3 to 50 Ton head) with a forged steel base and cylinder, 16 mm minimum toe clearance, built-in overload relief valve, spring-assisted return on 5T & 10T upright models, and 360° revolving housings on HTJ-20 models.



View Online & Get Quote ->

LIFTING CAPACITY	MIN ACCESS CLEARANCE	MAX LIFTING HEIGHT
2 - 25 Ton (Toe) / 3 - 50 Ton (Head)	16.0 - 58.0 mm Ultra-Low Toe Access	128 - 720 mm Extended Travel
HOUSING ARCHITECTURE	**SAFETY COMPLIANCE**	**RETURN MECHANISM**
Forged Steel Base & Cylinder (360° Revolving Housing on HTJ-20)	ANSI/ASME B30.1 & CE/GS Certified with Relief Valve	Spring-Assisted Return & Over-Travel Stop (5T & 10T Upright)

Model	Housing Configuration	Capacity		Minimum Height		Maximum Height		Weight [kg]
		Toe [Ton]	Top [Ton]	Toe [mm]	Top [mm]	Toe [mm]	Top [mm]	
HTJ-102	Standard Upright	2	3	16	238	128	349	8
HTJ-105	Standard Upright	5	6	22	298	141	409	24
HTJ-110	Standard Upright	10	14	28	333	173	460	38
HTJ-115	Standard Upright	15	30	32	345	185	500	48
HTJ-125	Standard Upright	20	50	40	390	215	530	75
HTJ-205	360° Revolving Housing	5	-	25	368	230	572	25
HTJ-210	360° Revolving Housing	10	-	30	420	260	650	35
HTJ-225	360° Revolving Housing	25	-	58	505	272	720	102