ULTRA-HIGH PRESSURE TENSIONER PUMPS | OEM CROSS-REFERENCE: ENERPAC ATP SERIES EQUIVALENT

HTP-A Series Pneumatic UHP Bolt Tensioner Pumps

Air-driven ultra-high pressure hydraulic bolt tensioner pumps rated for 1500 to 2500 Bar (21,750 to 36,250 PSI), engineered for spark-free flange bolting and hydraulic pulling across 4 to 8 L reservoirs.



View Online & Get Quote ->

MAX WORKING PRESSURE	DRIVE SOURCE	HYDRAULIC FLOW RATE
1500 to 2500 Bar (150 - 250 MPa)	6 - 10 Bar Compressed Air (Spark-Free Pneumatic)	0.10 - 0.40 L/min (Continuous High-Pressure)
OIL RESERVOIR	**HYDRAULIC OUTLET PORT**	**ENCLOSURE & MOBILITY**
4, 5, and 8 Liters Heavy-Gauge Reservoir	G-1/4" with High-Pressure Quick Coupler	Steel Frame w/ Dual Gauges & Air Filter-Regulator | 16-24 kg

Model Number	Max Pressure [Bar]	Required Air Input [Bar]	High-Pressure Flow Rate [L/min]	Dimensions (L×W×H) [mm]	Oil Capacity	Outlet Port Size	Weight [Kg]
HTP-A-1500	1500	6 - 10	0.4	600 × 460 × 500	4	G 1/4"	16
HTP-A-2100	2100	6 - 10	0.2	600 × 460 × 500	5	G 1/4"	24
HTP-A-3000	2500	6 - 10	0.1	600 × 460 × 500	8	G 1/4"	24