ULTRA-HIGH PRESSURE TENSIONER PUMPS | OEM CROSS-REFERENCE: ENERPAC EX-PROOF PUMPS EQUIVALENT

HTP-EX Series Explosion-Proof Electric Pumps

Two-stage explosion-proof electric bolt tensioner pump rated for 700 to 1800 Bar (Ex d IIB T4, IP55), engineered for ultra-high pressure bolting across Zone 1 and Zone 2 offshore oil, gas, and petrochemical facilities.



View Online & Get Quote ->

EXPLOSION-PROOF RATING **Ex d IIB T4 Flameproof / IP55 Protection**	OPERATING PRESSURE **700 - 1800 Bar (10,150 - 26,100 PSI) Adjustable**	MOTOR SPECIFICATION **0.75 kW Flameproof Three-Phase Motor (380V / 220V)**
TWO-STAGE FLOW RATE **Stage 1: 2.7 L/min (Rapid) | Stage 2: 0.4 L/min (UHP)**	RESERVOIR & DIMENSIONS **5.0 L Industrial Oil Reservoir | 468 × 442 × 604.5 mm**	NET OPERATING WEIGHT **37.0 kg Compact Protective Frame Construction**

Model	Max. Pressure [Bar]	Voltage	Flow Rate Output		Oil Capacity	Motor [kW]	Weight [kg]
			Stage 1 [L/min]	Stage 2 [L/min]			
HTP-EX-2000FBP	1800	380 / 220	2.7	0.4	5.0	0.75	37