TORQUE WRENCH DEDICATED PUMPS | OEM CROSS-REFERENCE: ENERPAC ZU4-4TW SERIES EQUIVALENT

HTW-P4E Series 4-Tool Compact Electric Torque Pumps

Two-stage compact electric hydraulic torque wrench pump rated for 700 Bar (10,000 PSI), powered by a 1.1 kW brushless motor (75 dB) to drive 2, 3, or 4 torque wrenches across wind turbine and petrochemical applications.



View Online & Get Quote ->

RATED PRESSURE
700 Bar (10,000 PSI) with Internal Relief Valve

MOTOR SPECIFICATION
1.1 kW High-Efficiency Brushless Motor (220V, 50/60 Hz)

NOISE RATING
75 dB Low Operating Noise Level

TWO-STAGE FLOW
Stage 1: 7.0 L/min (Rapid) | Stage 2: 0.8 L/min (High Pressure)

MANIFOLD CONFIGURATION
1 to 4 Outlet Ports (Order Suffix -2, -3, -4)

RESERVOIR & WEIGHT
5.0 L Oil Reservoir with Protective Frame, 22.0 kg

Model	Rated Pressure [Bar]	Voltage	Flow Rate Output		Oil Capacity	Power [kW]	Weight [kg]
			Stage 1 [L/min]	Stage 2 [L/min]			
HTW-P4E-2	700	220	7	0.8	5	1.1	22

Engineering Note: Pump can be configured with 1 to 4 outlet ports; append port suffix (-2, -3, -4) to model code when ordering (e.g., HTW-P4E-4 drives 4 torque wrenches simultaneously).