TORQUE WRENCH DEDICATED PUMPS | OEM CROSS-REFERENCE: ENERPAC ZA4T SERIES EQUIVALENT

HTW-PA Series Air-Driven High-Flow Torque Wrench Pumps

Air-driven three-stage hydraulic torque wrench pumps rated for 40 to 700 Bar (10,000 PSI), powered by a 1.1 kW air motor (4-8 Bar supply) with solenoid valve control, 8.0 L reservoir, and 20 kg compact frame.



View Online & Get Quote ->

RATED OPERATING PRESSURE
40 - 700 BAR (580 - 10,000 PSI)

AIR MOTOR DRIVE
1.1 KW AIR MOTOR (3,000 RPM @ 4-8 BAR, 1.9 M³/MIN)

THREE-STAGE DISPLACEMENT
7.0 / 1.6 / 0.8 L/MIN

RESERVOIR & WEIGHT
8.0 LITERS OIL RESERVOIR (20 KG WEIGHT)

VALVE & CONNECTION
SOLENOID VALVE CONTROL & TWIN-HOSE NPT 1/4" PORTS

EXHAUST ARCHITECTURE
EXTREME-ENVIRONMENT AIR OUTPORT & OIL/MIST SEGREGATION

Model	Pressure Output [Bar]	Air Input [Bar]	Air Consump. [m³/min]	Valve	Air Motor [kW]	Flow Rate Output			Oil Capacity	Out / Return Ports	Weight [kg]
						Stage 1 [L/min]	Stage 2 [L/min]	Stage 3 [L/min]			
HTW-PA-200Q	40-700	4-8	1.9	Solenoid	1.1 (3000 RPM)	7.0	1.6	0.8	8.0	1/4" NPT	20