VEHICLE-MOUNTED HEAVY DUTY PULLERS | OEM CROSS-REFERENCE: ENERPAC MOBILE BEARING PULLERS EQUIVALENT

HVP-W Series Wheel-Mounted Mobile Bearing Pullers

Double-acting wheel-mounted mobile hydraulic bearing pullers rated for 700 Bar (10,000 PSI), engineered for large shaft and hole-type workpiece disassembly across 50 to 500 Ton capacities.



View Online & Get Quote ->

RATED CAPACITY **50 - 500 Metric Tons**	OPERATING PRESSURE **700 Bar (10,000 PSI)**	CYLINDER ACTION **Double-Acting Powered Hydraulic Return**
STROKE RANGE **160 - 200 mm**	SPREAD & REACH **Spread 200-600 mm | Reach 300-480 mm**	MOBILE CHASSIS **Wheeled Cart with Onboard Hydraulic Lift**

Model Number	Pulling Capacity [Ton]	Spread [mm]	Reach [mm]	Stroke [mm]	Weight [kg]
HVP-W50	50	200 - 350	300	160	450
HVP-W100	100	230 - 450	340	160	540
HVP-W200	200	285 - 500	380	160	820
HVP-W300	300	350 - 550	450	200	953
HVP-W500	500	400 - 600	480	200	1800